

*COUNTY OF McCracken  
McCracken County Road Department  
3700 Coleman Road, Paducah, KY 42001*

*Phone (270) 442-9163      Fax (270) 443-0803      TDD 1-800-247-2510*

*PERMIT TO  
ALTER AND/OR REPAIR STREETS*

*Permission is hereby given to \_\_\_\_\_, to alter and/or repair \_\_\_\_\_,  
Located at \_\_\_\_\_,  
for the purpose of \_\_\_\_\_*

*The above name street(s) will be repaired in accordance with the attached County Road Specifications.*

<i>Estimated Cost</i>	<i>\$ _____</i>
<i>Estimated Completion Date</i>	<i>_____</i>
<i>Amount of Bond (if applicable)</i>	<i>\$ _____</i>

**NOTE: CONDITIONS OF PERMITS**

*The County will not be responsible for any future damage incurred to the utility by granting this permit. In the event the County request the utility be relocated, costs of work will be borne by the owner of the utility.*

*All paved driveways will be bored. All grassy areas of Right-of-Way will be restored to original, or better, condition within twelve (12) months of commencement of work.*

*Any cost from damage caused by the utility to the Right-of-Way, including road structure, will be borne by the owner of the utility.*

\_\_\_\_\_  
*Company Name*

\_\_\_\_\_  
*Signature of Contractor*

\_\_\_\_\_  
*Address*

\_\_\_\_\_  
*Phone*

*Approved by: \_\_\_\_\_  
General Foreman or Road Supervisor*

*Date: \_\_\_\_\_*

*This permit must be posted in job area, or with contractor, and after job is completed, returned to the McCracken County Road Department.*

*Roadway open-cuts will be backfilled with flowable-fill concrete within 4" of finished road surface. Finish the remainder with a 3000+ p.s.i. high-early strength concrete slab. Concrete surface to be broom finished and protected from traffic by steel plate cover for a minimum of 24 hours. No roadway will be closed overnight without General Foreman or Road Supervisor written permission. All traffic control barricades and signs required will meet the requirements of the "Manual on Uniform Traffic Control Devices".*

*All utilities will be a minimum of 42" under ditches and a minimum of 42" under pavement surfaces. All boring will be done by standard construction practices and by experienced personnel.*